

**\*\*CLEARANCE\*\* 5ft LED Strip Lights Non-corrosive IP65 Single 1500mm [1.5m]Vapour-proof**

**~~£111.61~~ £30.00**



**PRODUCT INFORMATION**

LED Type	SMD2835 LEDs
Warranty	No warranty on clearance products
Part L Compliant	Yes
Dimensions	1560mm x 120mm x 85mm
Weight	3.2kg
Equivalent to	1500mm Twin 58W T8

**TECHNICAL SPECIFICATIONS**

Power Consumption	56W
Input Voltage	110-280V AC
Power Factor	>0.95
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+40,000hrs
Ingress Protection	IP65
Emergency Battery Type	YUASA® 12V 1300mAh NiCd

**LUMEN PERFORMANCE**

Luminous Efficiency	120lm/W
Beam Angle	120°
CRI (Colour Rendering Index)	>75
Lumen Output	6700lm

**AVAILABLE OPTIONS**

Colour Temperature	Cool White (6500-7000K)
3-Hour Emergency Version	Yes
DMX 512 Compatible	No

**\*\*CLEARANCE\*\* 5ft LED Strip Lights Non-corrosive IP65 Single 1500mm [1.5m]Vapour-proof** A revolutionary LED replacement to replace complete non-corrosive fluorescent tube fittings in 1500mm / 5ft twin variety - 56W / 5,600lm. Utilising Epistar SMD2835 with direct illumination technology, prove advantageous over both conventional fluorescents and LED tube counterparts in terms of industry leading efficacy: 100lm/W. Hence an L70 rated lifetime of 30,000+ hour and simple

installation, this unit has proved to be the specifiers number one choice being deemed truly fit and forget. Wide demand throughout commercial and industrial sectors, namely workshops, high-humidity areas and even outbuildings use being IP65 weather-proof. Toughened polycarbonate diffuser for uniform lumen output with robust PC base. Unit comes complete with stainless steel side clips, detachable hinged tray for ease of install, fixing brackets and M20 x 1.5 IP65 cable gland. Options of 4ft/1200mm and 5ft/1500mm in single & twin variation. M3/NM3 emergency version includes internal built in 3-hour maintained emergency pack.