




Suspended Linear LED Light Up/Down Light 1200mm/4ft - Silver Anodised Aluminum (4,900lm) 52W Flicker Free




£132.00

4,900lm

**Direct/
Indirect
52W**



LEFT BACK VIEW OF FITTING



PRODUCT INFORMATION

LED Type	SMD2835 LEDs
Warranty	3 Year
Part L Compliant	Yes
Dimensions	1178mm x 90mm x 67mm
Weight	3.00kg
Equivalent to	2 x 36W T8

TECHNICAL SPECIFICATIONS

Power Consumption	52W
Input Voltage	110-280V AC
Power Factor	>0.95
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+45,000hrs
Ingress Protection	IP21

LUMEN PERFORMANCE

PRODUCT INFORMATION**TECHNICAL SPECIFICATIONS****LUMEN PERFORMANCE**

Luminous Efficiency	95lm/W
Beam Angle	120°
CRI (Colour Rendering Index)	>80Ra
Lumen Output	4,900lm (3,800lm:1100lm downlight:uplight)

AVAILABLE OPTIONS

Colour Temperature	Natural White (4000-4500K)
1-10V Dimmable	Available Variant
DALI Dimmable	Available Variant
DMX 512 Compatible	No

Suspended Linear LED Light for offices with both direct / indirect illumination. 1200mm / 4ft 52W Suspended Light for office, public open spaces and retail with high lumen output of 4,900 lumens in Natural White 4000K (4800lm:1100lm uplight:downlight). Modern minimalist interior design highly suited by suspended luminaire. Finished in a choice of colours: stylish 6063 silver aluminum housing, enclosing an Frosted diffuser for subtle light output suiting a wide range of modern commercial and institutional applications, including hallways, retail & conference rooms. 1200mm linear design with a superior lumen output up to 4,900lm for ample lux levels across a range of environments - can be continuous with additional bracket. In-fils available on request. High CRI combined with stylish design make this unit perfectly suited to retail applications. Further options of dimmable: DALI and 1-10V.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)