





LED Recessed Canopy Light for Petrol Station Forecourt - IP65 150W / 400W SON / 250W MHL

£304.57



PRODUCT INFORMATION

LED Type SMD3030 LEDs

Warranty 5 Year
Part L Compliant Yes

Dimensions 350mm x 426mm x 72mm

Weight 6.7kg
Socket Type N/A
Equivalent to 400W SON

TECHNICAL SPECIFICATIONS

Power Consumption 150W
Input Voltage 110-280V AC
Power Factor >0.95

Operating Temperature -20°C to 50°C L70 Rated Lifetime +50,000hrs Ingress Protection IP65

LUMEN PERFORMANCE

Luminous Efficiency110lm/WBeam Angle90° x 90°CRI (Colour Rendering Index)>80RaLumen Output16,500lm

AVAILABLE OPTIONS

Colour Temperature Pure White (5000K)

3-Hour Emergency Version No Built-in Microwave Occupancy Detector No

1-10V Dimmable Available on Request DALI Dimmable Available on Request

LED Recessed canopy light designed specifically industrial and exterior recessed ceiling canopies such as fuel stations, industrial clean-room applications and others. Finished in a rugged RAL White powder coated aluminium housing with



Unit 2,
Delta Court,
Doncaster,
DN9 3GN
text_phone 03333 444 943

tempered, stabilised, impact resistant PMMA lens, the recessed canopy luminaire is suitable: for hextreme climates & eledstore.co/ environments from -20°C to +50°C.

A range of lumen packages from 60W - 150W, up to 19,000lm hence suitable for mount heights up to 12m - making a suitable direct replacement for 400W SON fittings energy efficient low luminous decay and maintenance were key factors in the luminaire design, meaning annual re-lamp, expensive lift equipment and inconvenience is negligible, as well as a much sought after energy savings of 75%.

Durable with rated life span of +50,000 hours / No UV or IR emissions / Instant on & Flicker free / CE & RoHS international standards / Environmentally friendly & part recyclable: no mercury or other hazardous materials used / RAL White powder coated aluminium heat sink / PMMA optics / Meanwell™ HLG Driver.