


LED Premium Street Light 60w - 4-6m Column Street Lighting Fixture - Dark Sky Friendly 3000K/4000K 0% ULOR

£126.46

8,400lm

60W
Replaces
100W SON



DARK SKY FRIENDLY



3000K*



PRODUCT INFORMATION

| | |
|------------------|----------------------------|
| LED Type | SMD3030 LEDs |
| Warranty | 5 Year |
| Part L Compliant | Yes |
| Dimensions | 617mm x 212mm x 118mm |
| Weight | 5.35kg |
| Windage | 0.13m² |
| Socket Type | Optional 3 pin NEMA Socket |

PRODUCT INFORMATION

Equivalent to 70 MHL

TECHNICAL SPECIFICATIONS

| | |
|-----------------------|---------------|
| Power Consumption | 60W |
| Input Voltage | 100-280V AC |
| Power Factor | >0.96 |
| Operating Temperature | -20°C to 65°C |
| L70 Rated Lifetime | +100,000hrs |
| Ingress Protection | IP66 |

LUMEN PERFORMANCE

| | |
|------------------------------|------------|
| Luminous Efficiency | 140lm/W |
| Beam Angle | 80° x 150° |
| CRI (Colour Rendering Index) | >80Ra |
| Lumen Output | 8,400lm |

AVAILABLE OPTIONS

| | |
|---------------------------------------|--|
| Colour Temperature | 3000K (Dark Sky Friendly- 0% ULOR) 4000K |
| 3-Hour Emergency Version | No |
| Built-in Microwave Occupancy Detector | No |
| 1-10V Dimmable | Available on Request |
| DALI Dimmable | Available on Request |

Luminaire designed for column/post mounting at heights of 4 - 16m, with a range of sizes across 30W - 240W (4,200-33,000lm). IP66 design for exterior environments, with a low profile, sleek silver anodised aluminum body for harsh weather environments, Premium Street light is for urban applications such as car-parks, pathways and pedestrian areas. PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further enhancing this 140lm/W luminaire to give optimum lux levels through out. Furthermore the Premium Street light is compatible with standard mains photocells. Additional benefits include 100,000 hours maintenance free performance, with no-tools/quick release access to the internal control gear for installation. Unit available with either 60mm or 76mm entry bracket for both bottom & side-entry hence universally compatible. Angle of illumination can be adjusted around 10° for increased spread. Slate Grey RAL 7015.



[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

Unit 2,
Delta Court,
Doncaster,
DN9 3GN
text_phone 03333 444 943
sales@theledstore.co | <https://theledstore.co/>