

**LED Premium Street Light 30w c/w Photocell NEMA Dusk til Dawn Sensor  
Flicker Free**

**£133.63**



**4,200lm**



**30W**  
Replaces  
**35W SOX**



**LED Premium Street Light DIMENSIONS**



**PHOTOCELL ENABLED**  
FOR UP TO 80% SAVINGS ON ELECTRICITY

**DURABLE, ROBUST AND DEPENDABLE**  
LONG LASTING PERFORMANCE

Impact tested  
Vibration tested  
Lifetime: 100,000+ Hours

OPTIONAL  
Dusk-to-Dawn sensor  
Shorting Cap



**24/7 CUSTOMER SUPPORT**

**LED Premium Street Light**  
Slim and elegant aesthetics  
Superior efficacy up to 140 lm/W  
Wide range of lumen packages  
Self-cleaning Smooth Surface  
Tool-less Access



**INSTALLATION INSTRUCTIONS:**

1. Remove the photocell sensor cap.
2. Mount the photocell sensor to the back of the light fixture.
3. Mount the light fixture to the pole using the provided brackets.
4. Tighten the mounting screws.
5. Connect the power wires to the terminals on the back of the light fixture.
6. Turn the photocell sensor to the desired beam angle.

**INSTALLATION INSTRUCTIONS:**

1. Remove the photocell sensor cap.
2. Mount the photocell sensor to the back of the light fixture.
3. Mount the light fixture to the pole using the provided brackets.
4. Tighten the mounting screws.
5. Connect the power wires to the terminals on the back of the light fixture.
6. Turn the photocell sensor to the desired beam angle.

**DARK SKY FRIENDLY**

**3000K\***

ULDR 8%

**Free Lighting Design Service**

Unsure of how many lights you require?  
Can't see about layout, tilt levels and beam?  
Don't worry, our expert lighting designers are here to help.  
Enquire about our **FREE** no obligation lighting design service.  
Turned around & within just 48 hours!



**PRODUCT INFORMATION**

Body Colour	Slate Grey RAL 7015
LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	617mm x 212mm x 118mm
Weight	3.85kg
Windage	0.08m <sup>2</sup>

**PRODUCT INFORMATION**

Socket Type	Optional 3 pin NEMA Socket
Equivalent to	35 SOX
<b>TECHNICAL SPECIFICATIONS</b>	
Power Consumption	30W
Input Voltage	100-280V AC
Power Factor	>0.96
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+100,000hrs
Ingress Protection	IP66
<b>LUMEN PERFORMANCE</b>	
Luminous Efficiency	140lm/W
Beam Angle	150° x 80°
CRI (Colour Rendering Index)	>80Ra
Lumen Output	4,200lm
<b>AVAILABLE OPTIONS</b>	
Colour Temperature	3000K (Dark Sky Friendly- 0% ULOR) 4000K
3-Hour Emergency Version	No
Built-in Microwave Occupancy Detector	No
1-10V Dimmable	Available on Request
DALI Dimmable	Available on Request

\*\*Fitting Comes inclusive with integral 3-Pin NEMA Socket and Lucy Zodion 70lux Photocell\*\*

Luminaire designed for column/post mounting at heights of 4 - 16m, with a range of sizes across 30W - 240W (4,200-33,000lm), IP66 design for exterior environments, with a low profile, sleek silver anodised aluminum body for harsh weather environments, Premium Street light is for urban applications such as car-parks, pathways and pedestrian areas. PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further

enhancing this 140lm/W luminaire to give optimum lux levels through out. Furthermore the Premium Street light is compatible with standard mains photocells. Additional benefits include 100,000 hours maintenance free performance, with no-tools/quick release access to the internal control gear for installation. Unit available with either 60mm or 76mm entry bracket for both bottom & side-entry hence universally compatible. Angle of illumination can be adjusted around 10° for increased spread. Slate Grey RAL 7015.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)