

## LED Premium Street Light 30w c/w Photocell NEMA Dusk til Dawn Sensor Flicker Free

**£133.63**


**4,200lm**



**30W**  
Replaces  
**35W SOX**








### LED Premium Street Light DIMENSIONS



### Performance-Optimized Design & Robust Construction

For 100,000+ Hours & 50,000+ Cycles



### PRODUCT INFORMATION

LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	617mm x 212mm x 118mm
Weight	3.85kg
Windage	0.08m <sup>2</sup>
Socket Type	Optional 3 pin NEMA Socket

## PRODUCT INFORMATION

Equivalent to 35 SOX

### TECHNICAL SPECIFICATIONS

Power Consumption 30W  
Input Voltage 100-280V AC  
Power Factor >0.96  
Operating Temperature -20°C to 50°C  
L70 Rated Lifetime +100,000hrs  
Ingress Protection IP66

### LUMEN PERFORMANCE

Luminous Efficiency 140lm/W  
Beam Angle 150° x 80°  
CRI (Colour Rendering Index) >80Ra  
Lumen Output 4,200lm

### AVAILABLE OPTIONS

Colour Temperature 3000K (Dark Sky Friendly- 0% ULOR) 4000K  
3-Hour Emergency Version No  
Built-in Microwave Occupancy Detector No  
1-10V Dimmable Available on Request  
DALI Dimmable Available on Request

**\*\*Fitting Comes inclusive with integral 3-Pin NEMA Socket and Lucy Zodion 70lux Photocell\*\***

Luminaire designed for column/post mounting at heights of 4 - 16m, with a range of sizes across 30W - 240W (4,200-33,000lm), IP66 design for exterior environments, with a low profile, sleek silver anodised aluminum body for harsh weather environments, Premium Street light is for urban applications such as car-parks, pathways and pedestrian areas. PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further enhancing this 140lm/W luminaire to give optimum lux levels through out. Furthermore the Premium Street light is compatible with standard mains photocells. Additional benefits include 100,000 hours maintenance free performance, with no-tools/quick release access to the internal control gear for installation. Unit available with either 60mm or 76mm entry bracket for both

bottom & side-entry hence universally compatible. Angle of illumination can be adjusted around 10° for increased spread.  
Slate Grey RAL 7015.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)