

LED Premium Street Light 40w c/w Photocell NEMA Dusk til Dawn Sensor

£145.08


5,600lm




40W
Replaces
70W SON



LED Premium Street Light DIMENSIONS



Performance-Optimized Design & Robust Construction
For MAXIMUM VALUE & MAXIMUM LIFE EXPECTANCY



PHOTOCELL ENABLED
FOR UP TO 20% SAVINGS ON ELECTRICITY

DURABLE, ROBUST AND DEPENDABLE
LONG-LETTING PERFORMANCE

Optional features: Dusk-to-Dawn sensor, Shorting Cap, Impact tested, Vibration tested, Lifetime 100,000 hours.



24/7 CUSTOMER SUPPORT

LED Premium Street Light
Slim and elegant aesthetics
Superior efficacy up to 140 lm/W
Wide range of luminaire packages
Self-cleaning Smooth Surface
Tool-less Access



INSTALLATION INSTRUCTIONS:

1. Mounting bracket to the pole.
2. Mounting the luminaire to the bracket.
3. Mounting the photocell sensor to the luminaire.
4. Mounting the luminaire to the pole.
5. Mounting the luminaire to the pole.
6. Mounting the luminaire to the pole.

INSTALLATION INSTRUCTIONS:

7. Mounting the luminaire to the pole.
8. Mounting the luminaire to the pole.
9. Mounting the luminaire to the pole.
10. Mounting the luminaire to the pole.
11. Mounting the luminaire to the pole.
12. Mounting the luminaire to the pole.

Free Lighting Design Service

unsure of how many lights you require?
Confused about layout, luminaire and lumens?
Don't worry, our expert lighting designers are here to help!
*Requires about our FREE no-obligation lighting design service.
Turned around & within just 48 hours.

DARK SKY FRIENDLY



3000K*

PRODUCT INFORMATION

Body Colour	Slate Grey RAL 7015
LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	617mm x 212mm x 118mm
Weight	3.85kg
Windage	0.08m ²
Socket Type	Optional 3 pin NEMA Socket

PRODUCT INFORMATION

Equivalent to 70 SON

TECHNICAL SPECIFICATIONS

Power Consumption 40W
 Input Voltage 100-280V AC
 Power Factor >0.96
 Operating Temperature -20°C to 50°C
 L70 Rated Lifetime +100,000hrs
 Ingress Protection IP66

LUMEN PERFORMANCE

Luminous Efficiency 140lm/W
 Beam Angle 150° x 80°
 CRI (Colour Rendering Index) >80Ra
 Lumen Output 5,600lm

AVAILABLE OPTIONS

Colour Temperature 3000K (Dark Sky Friendly- 0% ULOR) 4000K
 3-Hour Emergency Version No
 Built-in Microwave Occupancy Detector No
 1-10V Dimmable Available on Request
 DALI Dimmable Available on Request

****Fitting Comes inclusive with integral 3-Pin NEMA Socket and Lucy Zodion 70lux Photocell****

Luminaire designed for column/post mounting at heights of 4 - 16m, with a range of sizes across 30W - 240W (4,200-33,000lm), IP66 design for exterior environments, with a low profile, sleek silver anodised aluminum body for harsh weather environments, Premium Street light is for urban applications such as car-parks, pathways and pedestrian areas. PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further enhancing this 140lm/W luminaire to give optimum lux levels through out. Furthermore the Premium Street light is compatible with standard mains photocells. Additional benefits include 100,000 hours maintenance free performance, with no-tools/quick

release access to the internal control gear for installation. Unit available with either 60mm or 76mm entry bracket for both bottom & side-entry hence universally compatible. Angle of illumination can be adjusted around 10° for increased spread. Slate Grey RAL 7015.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)