

## LED Premium Street Light 50w c/w Photocell NEMA Dusk til Dawn Sensor Flicker Free

**£157.86**

**7,000lm**



**50W**  
Replaces  
**70W MHL**



### LED Premium Street Light DIMENSIONS



### PHOTOCELL ENABLED

FOR UP TO 80% SAVINGS ON ELECTRICITY




### DURABLE, ROBUST AND DEPENDABLE


GUARANTEED HIGH PERFORMANCE



OPTIONAL



### 24/7 CUSTOMER SUPPORT



### DARK SKY FRIENDLY



3000K\*

### PRODUCT INFORMATION

Body Colour	Slate Grey RAL 7015
LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	617mm x 212mm x 118mm
Weight	3.85kg
Windage	0.08m <sup>2</sup>

Slate Grey RAL 7015

SMD3030 LEDs

5 Year

Yes

617mm x 212mm x 118mm

3.85kg

0.08m<sup>2</sup>

Socket Type	Optional 3 pin NEMA Socket
Equivalent to	70 SON

**TECHNICAL SPECIFICATIONS**

Power Consumption	50W
Input Voltage	100-280V AC
Power Factor	>0.96
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+100,000hrs
Ingress Protection	IP66

**LUMEN PERFORMANCE**

Luminous Efficiency	140lm/W
Beam Angle	150° x 80°
CRI (Colour Rendering Index)	>80Ra
Lumen Output	7,000lm

**AVAILABLE OPTIONS**

Colour Temperature	3000K (Dark Sky Friendly- 0% ULR) 4000K
3-Hour Emergency Version	No
Built-in Microwave Occupancy Detector	No
1-10V Dimmable	Available on Request
DALI Dimmable	Available on Request

\*\*Fitting Comes inclusive with integral 3-Pin NEMA Socket and Lucy Zodion 70lux Photocell\*\*

Luminaire designed for column/post mounting at heights of 4 - 16m, with a range of sizes across 20W - 240W (2,800-33,000lm), IP66 design for exterior environments, with a low profile, sleek silver anodised aluminum body for harsh weather environments, Premium Street light is for urban applications such as car-parks, pathways and pedestrian areas. PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further

enhancing this 140lm/W luminaire to give optimum lux levels through out. Furthermore the Premium Street light is compatible with standard mains photocells. Additional benefits include 100,000 hours maintenance free performance, with no-tools/quick release access to the internal control gear for installation. Unit available with either 60mm or 76mm entry bracket for both bottom & side-entry hence universally compatible. Angle of illumination can be adjusted around 10° for increased spread. Slate Grey RAL 7015.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)