

**LED Premium Street Light 20w - 3-6M Column Street Lighting Fixture - Dark Sky Friendly 3000K/4000K 0% ULOR**



**£87.67**

**2,800lm**

**20W**  
Replaces  
**35W SOX**



**LED Premium Street Light DIMENSIONS**



**PHOTOCELL ENABLED**  
FOR UP TO 80% SAVINGS ON ELECTRICITY

Dusk-to-Dawn sensor  
Shorting Cap

OPTIONAL

**DURABLE, ROBUST AND DEPENDABLE**  
LONG LASTING PERFORMANCE

Impact tested  
Vibration tested  
Lifetime 100,000+ Hours



**24/7 CUSTOMER SUPPORT**

LED Premium Street Light  
Slim and elegant aesthetics  
Superior efficacy up to 140 lm/W  
Wide range of lumen packages  
Self-cleaning Smooth Surface  
Tool-less Access

**Free Lighting Design Service**

Unsure of how many lights you require?  
Can't see about layout, tilt levels and lumens?  
Don't worry, our expert lighting designers are here to help.

Enquire about our **FREE** no obligation lighting design service.  
Turned around & within just 48 hours!

**INSTALLATION INSTRUCTIONS:**

**INSTALLATION INSTRUCTIONS:**

**DARK SKY FRIENDLY**

ULOR 0%  
**3000K\***

**PRODUCT INFORMATION**

LED Type  
Warranty  
Part L Compliant  
Dimensions  
Weight  
Windage  
Socket Type

SMD3030 LEDs  
5 Year  
Yes  
617mm x 212mm x 118mm  
3.85kg  
0.08m<sup>2</sup>  
Optional 3 pin NEMA Socket

**PRODUCT INFORMATION**

Equivalent to 70 SON

**TECHNICAL SPECIFICATIONS**

Power Consumption 20W  
 Input Voltage 100-280V AC  
 Power Factor >0.96  
 Operating Temperature -20°C to 50°C  
 L70 Rated Lifetime +100,000hrs  
 Ingress Protection IP66

**LUMEN PERFORMANCE**

Luminous Efficiency 140lm/W  
 Beam Angle 150° x 80°  
 CRI (Colour Rendering Index) >80Ra  
 Lumen Output 2,800lm

**AVAILABLE OPTIONS**

Colour Temperature 3000K (Dark Sky Friendly- 0% ULOR) 4000K  
 3-Hour Emergency Version No  
 Built-in Microwave Occupancy Detector No  
 1-10V Dimmable Available on Request  
 DALI Dimmable Available on Request

Luminaire designed for column/post mounting at heights of 4 - 16m, with a range of sizes across 30W - 240W (4,200-33,000lm), IP66 design for exterior environments, with a low profile, sleek silver anodised aluminium body for harsh weather environments, Premium Street light is for urban applications such as car-parks, pathways and pedestrian areas. PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further enhancing this 140lm/W luminaire to give optimum lux levels through out. Furthermore the Premium Street light is compatible with standard mains photocells. Additional benefits include 100,000 hours maintenance free performance, with no-tools/quick release access to the internal control gear for installation. Unit available with either 60mm or 76mm entry bracket for both bottom & side-entry hence universally compatible. Angle of illumination can be adjusted around 10° for increased spread. Slate Grey RAL 7015.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)



Unit 2,  
Delta Court,  
Doncaster,  
DN9 3GN  
text\_phone 03333 444 943  
sales@theledstore.co | <https://theledstore.co/>

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)