





# LED Street Light - Victorian / Traditional Street Light Luminaire 30W/40W/50W - c/w Photocell Dusk Til Dawn DayLight Sensor NEMA Socket Flicker Free

£274.63 £263.18



## **PRODUCT INFORMATION**

Body Colour RAL9005 Matt Black LED Type SMD3030 LEDs

Warranty 5 Year
Part L Compliant Yes

Dimensions 870mm x 440mm x 440mm

Weight 7.1kg Windage 0.16m $^2$  Equivalent to 70 SON / MHL

## **TECHNICAL SPECIFICATIONS**

Power Consumption 30W/40W/50W Input Voltage 100-280V AC Power Factor >0.96 Operating Temperature -20°C to 50°C

Operating Temperature -20°C to 50°C L70 Rated Lifetime +55,000hrs Ingress Protection IP65

# **LUMEN PERFORMANCE**

Luminous Efficiency 115lm/W

Beam Angle 120° (All-round-optic)

CRI (Colour Rendering Index) >80Ra

Lumen Output 3,500lm/4,600lm/5,600lm

# **AVAILABLE OPTIONS**



**PRODUCT INFORMATION** 

Unit 2,
Delta Court,
Doncaster,
DN9 3GN
text\_phone 03333 444 943
sales@theledstore.co | https://theledstore.co/

### **TECHNICAL SPECIFICATIONS**

### **LUMEN PERFORMANCE**

### **AVAILABLE OPTIONS**

Colour Temperature 3000K (Dark Sky Friendly- 0% ULOR) 4000K

3-Hour Emergency Version No Built-in Microwave Occupancy Detector No

1-10V Dimmable Available on Request
DALI Dimmable Available on Request

\*\*EACH LIGHT HAS A BUILT IN 76MM-TO-60MM REDUCER - PLEASE NOTE THIS IS AN OPEN FITTING (NO GLASS)\*\*

\*\*Fitting Comes inclusive with integral 3-Pin NEMA Socket and Lucy Zodion 70lux Photocell\*\*

The Victorian post-top is a traditional looking LED luminaire designed for column/post mounting at heights of between 4 - 8m. It has an IP65 design for suitable exterior environments with traditional aesthetic character, such as urbancentres, pathways and pedestrian areas. The unit features a toughened glass diffuser which protects the LED chips and provides a high uniformity across a range of spaces and reduced light spillage, thus further enhancing this 115lm/W luminaire to give optimum lux levels throughout. The luminaire is powered by a high efficiency Meanwell™ Driver and furthermore, is compatible with standard mains photocells.

Additional benefits as well include a +55,000 hour maintenance free performance, minimal disturbance to nocturnal wildlife due to the lack of UV/IR spectrum associated with LED photometric characteristics. The unit is complete with base mount for 76mm column-entry hence universally compatible.

## **Product information**

Durable with rated life span of +55,000 hours / No UV or IR emissions / Instant Illumination & Flicker free / CE & RoHS international standards / Environmentally friendly & part recyclable: no mercury or other hazardous materials used / Heavy duty die-cast aluminium housing & 2mm toughened glass lens / Complies with EN60598.

**DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE**