

**LED Street Light - Victorian / Traditional Street Light Luminaire 50W - c/w  
Photocell Dusk Til Dawn DayLight Sensor NEMA Socket Flicker Free**

**£274.63 £263.18**



**PRODUCT INFORMATION**

LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	870mm x 440mm x 440mm
Weight	7.1kg
Windage	0.16m <sup>2</sup>
Equivalent to	70 SON / MHL

**TECHNICAL SPECIFICATIONS**

Power Consumption	50W
Input Voltage	100-280V AC
Power Factor	>0.96
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+55,000hrs
Ingress Protection	IP65

**LUMEN PERFORMANCE**

Luminous Efficiency	115lm/W
Beam Angle	120° (All-round-optic)
CRI (Colour Rendering Index)	>80Ra
Lumen Output	5,600lm

**AVAILABLE OPTIONS**

Colour Temperature	3000K (Dark Sky Friendly- 0% ULOR) 4000K
--------------------	--

## PRODUCT INFORMATION

## TECHNICAL SPECIFICATIONS

## LUMEN PERFORMANCE

### AVAILABLE OPTIONS

3-Hour Emergency Version	No
Built-in Microwave Occupancy Detector	No
1-10V Dimmable	Available on Request
DALI Dimmable	Available on Request

**\*\*EACH LIGHT HAS A BUILT IN 76MM-TO-60MM REDUCER - PLEASE NOTE THIS IS AN OPEN FITTING (NO GLASS)\*\***

**\*\*Fitting Comes inclusive with integral 3-Pin NEMA Socket and Lucy Zodion 70lux Photocell\*\***

The Victorian post-top is a traditional looking LED luminaire designed for column/post mounting at heights of between 4 - 8m. It has an IP65 design for suitable exterior environments with traditional aesthetic character, such as urban-centres, pathways and pedestrian areas. The unit features a toughened glass diffuser which protects the LED chips and provides a high uniformity across a range of spaces and reduced light spillage, thus further enhancing this 115lm/W luminaire to give optimum lux levels throughout. The luminaire is powered by a high efficiency Meanwell™ Driver and furthermore, is compatible with standard mains photocells.

Additional benefits as well include a +55,000 hour maintenance free performance, minimal disturbance to nocturnal wildlife due to the lack of UV/IR spectrum associated with LED photometric characteristics. The unit is complete with base mount for 76mm column-entry hence universally compatible.

### Product information

Durable with rated life span of +55,000 hours / No UV or IR emissions / Instant Illumination & Flicker free / CE & RoHS international standards / Environmentally friendly & part recyclable: no mercury or other hazardous materials used / Heavy duty die-cast aluminium housing & 2mm toughened glass lens / Complies with EN60598.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)