





LED Eco High Bay Light 100W Low Bay - Warehouse Industrial UFO Fitting - 250W SON Replacement Flicker Free

£57.00 £49.50











LED UFO High Bay DIMENSIONS







PRODUCT INFORMATION

LED Type Philips Lumileds LUXEON® SMD 2835 Leds

Warranty 3 Year
Part L Compliant Yes

Dimensions Ø270mm x 160mm

Weight 3.5kg
Equivalent to 250W SON

TECHNICAL SPECIFICATIONS

Power Consumption 100W

Input Voltage 100-280V AC Power Factor >0.95

Operating Temperature -20°C to 50°C L70 Rated Lifetime +100,000hrs

Ingress Protection IP65

LUMEN PERFORMANCE

Luminous Efficiency135lm/WBeam Angle90°CRI (Colour Rendering Index)>80RaLumen Output13,000lm

AVAILABLE OPTIONS

Colour Temperature Natural White 4000K

3-Hour Emergency Version No Built-in Microwave Occupancy Detector No

1-10V Dimmable Available on Request

LED Eco High Bay Light 100W Low Bay - Warehouse Industrial UFO Fitting are designed specifically for installations requiring high level light mounting from 6 - 12m. With industrial applications in mind, these units replace up to 400W metal halide type



Unit 2,
Delta Court,
Doncaster,
DN9 3GN
text_phone 03333 444 943

fittings: with the added benefit of 75% energy savings, improved lumen performance & improved @Rio(ColourtRendering tore.co/ Index: ideal in packing warehouses), as well as long life meaning annual re-lamp & expensive lift equipment/inconvenience is negligible.

The UFO Series is available in 3 options: 100W/150W/200W, comprised of high performance Lumileds LUXEON® SMD 2835 LEDs. Manufactured from die-cast aluminium with a matt black finish, the housing provides strong protection, durability and heat dissipation for the LEDs. The toughened glass diffuser greatly reduces glare and the Nano-material reflector further enhances efficacy up to 125lm/W in a standard colour temperature of 4000K (others on request).

Further options include dimmable options: 1-10V

Durable with a rated life span of +100,000 hours / No UV or IR emissions / Instant on & Flicker free / CE & RoHS international standards / Environmentally friendly & part recyclable: no mercury or other hazardous materials used / One-piece Die cast aluminium heat sink / Toughened Glass optic lens / Mounting options of Mounting Hook or Surface Mount Bracket.

DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE