

5m Aluminium Conical / Tapered Lamp Post / Lighting Column Flange Plated Bolt Down - Machine Brushed Aluminium Street Lamp Post 5 Metre (5m Above Ground)

£396.00 £307.00



5m Aluminium Conical Lamp Post / Lighting Column Flange Plated Bolt Down - Machine Brushed Aluminium Street Lamp Post 5 Metre (5m Above Ground) suitable for road, residential, CCTV/security features and general amenity areas, with street lanterns, floodlights & post top amenity luminaires (please see related accessories) Designed to BSEN 40








PLEASE NOTE - Weight & Windage must be checked for suitability of the column against the installation postcode. Please email us for more information prior to purchase. It is the responsibility of the installer to ensure columns are installed safely and correctly, no liability will be accepted by The LED Store/supplier. In certain cases a ground survey may be required prior to installation. . Unit does not include column door key. Please find the link to this product below.

NOTE - if bolting down the flange plate with steel bolts or fitting mild steel brackets, you must use a separation membrane / barrier between the 2 materials such as a plastic sleeve, washers, gasket etc, to prevent cross contamination and corrosion between to the aluminium and steel.

[TORX COLUMN DOOR KEY](#)

NOTE* - The above is only a typical detail & is subject to ground conditions & head weight / windage load - we advise this is checked prior to installation

Flange Plate Mounted

| Dimensions (mm) |  |  |  |  |  |  |  |
|-----------------------|---|---|---|---|--|---|---|
| Product Code | Height | D1 | D2 | Door Opening | Flange Plate | Weight (kg) | Concrete Dimension* |
| SDACOL4M76MMFP | 4m | 76 | 140 | 600x100 | Type 4 | 29.0 | 650 x 750 |
| SDACOL5M76MMFP | 5m | 76 | 140 | 600x100 | Type 4 | 32.0 | 650 x 750 |
| SDACOL6M76MMFP | 6m | 76 | 152 | 600x100 | Type 4 | 38.0 | 650 x 750 |

*Concrete dimension based on a minimum ground bearing pressure of 150kN/m², (S = square dimension, H = depth)

NOTE - The above is only a typical detail & is subject to ground conditions & head weight / windage load - we advise this is checked prior to installation