
Unit 2,
Delta Court,
Doncaster,
DN9 3GN
text_phone 03333 444 943
sales@theledstore.co | https://theledstore.co/

LED Panhead Post-Top Street Light (60W - 150W) - 360 Degree Car Park / Street Light Lantern c/w 76mm Entry c/w Nema Socket + Photocell Dusk-til Dawn Sensor

~~£440.40~~ £289.58



PRODUCT INFORMATION

LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	Ø610mm x 235mm
Weight	10.7kg
Windage	0.14m²
Equivalent to	70 SON / MHL

TECHNICAL SPECIFICATIONS

Power Consumption	60W / 90W / 120W / 150W
Input Voltage	100-280V AC
Power Factor	>0.95
Operating Temperature	-20°C to 65°C
L70 Rated Lifetime	+100,000hrs
Ingress Protection	IP65

LUMEN PERFORMANCE

Luminous Efficiency	140lm/W
Beam Angle	150° x 150° (All-round-optic)
CRI (Colour Rendering Index)	>80Ra
Lumen Output	60W 8,400lm 90W 12,600lm 120W 16,800lm 150W 21,000lm

Unit 2,
Delta Court,
Doncaster,
DN9 3GN
text_phone 03333 444 943
sales@theledstore.co | https://theledstore.co/

PRODUCT INFORMATION

TECHNICAL SPECIFICATIONS

LUMEN PERFORMANCE

AVAILABLE OPTIONS

Colour Temperature	3000K (Dark Sky Friendly- 0% ULOR) 4000K
3-Hour Emergency Version	No
Built-in Microwave Occupancy Detector	No
1-10V Dimmable	Available on Request
DALI Dimmable	Available on Request

LED Panhead Post-Top Street Light (60W - 150W) - 360 Degree Car Park / Street Light Lantern c/w 76mm Entry c/w Nema Socket + Photocell Dusk-til Dawn Sensor

The Panhead Series post-top offers high-quality lighting, creating a safe and pleasant visual experience from column/post mounting at 3-10m high, suited to general open areas such as pedestrian areas, car parks and low-to-medium traffic urban applications. The minimalist and modern design provides an aesthetic continuity while generating massive energy savings.

With a high tightness level and a very high degree of impact resistance, this luminaire is built to withstand harsh environmental conditions and vandalism to perform over time. High-pressure die cast aluminium housing finished with 5mm tempered prismatic glass, the Panhead luminaire gives all round uniform illumination while remains dark sky friendly, capable for reaching 20-30lux from typical 6-8m installations. The luminaire ensures photometric performance and visual comfort to offer safety and well-being in the public space. Furthermore, the luminaire is compatible with standard external mains photocells for dusk-till-dawn control.

The unit is complete with base mount suitable for 76mm post top entry hence universally compatible. Additional benefits include 140m/W efficacy, +100,000 hour maintenance free performance, no-tools/quick release access to internal gear tray for maintenance, and the hinge mechanism further secured with stainless steel safety strap.

Unit 2,
Delta Court,
Doncaster,
DN9 3GN
text phone 03333 444 943



Standard 3/7 pin NEMA available or Zhaga sockets on request



Centrally mounted luminaire with 360° light distribution



Suitable for Ø76mm column entry

Product information

Durable with rated life span L70>100,000 hours / No UV or IR emissions / Instant Illumination & flicker free / UKCA, CE & RoHS international standards / Environmentally friendly & part recyclable: no mercury or other hazardous materials used / Heavy duty die-cast aluminium housing & 5mm prismatic tempered glass / Available in DALI or 1-10V dimmable and PLC control systems / Complies with EN60598

Code	Nominal Size	Power Consumption	Lumen Output	Nett Weight	Windage
SDPHPT-060	Ø610mm x 235mm	60W	8,400lm	10.7kg	0.14m²
SDPHPT-090	Ø610mm x 235mm	90W	12,600lm	10.7kg	0.14m²
SDPHPT-120	Ø610mm x 235mm	120W	16,800lm	11.2kg	0.14m²
SDPHPT-150	Ø610mm x 235mm	150W	21,000lm	11.2kg	0.14m²

Technical Specification

Beam Angle: 150°x 150°(All-round-optic) Luminous Efficacy: 140lm/W
Input Voltage: 100-277VAC
Color Rendering Index: 80Ra

LED Type: LM80 3030LEDs
Operating Temperature: -20°C to 50°C

Power Factor: 0.95
Mounting Height: 3-10m
Color Temperature: 3000K (Dark Sky Friendly) / 4000K

(Others available on request)