

sales@theledstore.co/ https://theledstore.co/



CLEARANCE 50W LED Post Top Lantern - 360 Degree Car Park / Street Light **Luminaire 50W 76mm Entry**

£253.80 £118.80



PRODUCT INFORMATION

LED Type SMD3030 LEDs

Warranty No warranty on clearance products

Part L Compliant

Dimensions Ø525mm x 525mm

Weight 6.6kg Windage $0.13m^{2}$ 70 SON / MHL Equivalent to

TECHNICAL SPECIFICATIONS

50W **Power Consumption**

Input Voltage 100-280V AC **Power Factor** >0.95

Operating Temperature -20°C to 65°C L70 Rated Lifetime +55,000hrs **Ingress Protection** IP65

LUMEN PERFORMANCE

Luminous Efficiency 120lm/W

150° x 150° (All-round-optic) Beam Angle

CRI (Colour Rendering Index) >80Ra 6,000lm Lumen Output

AVAILABLE OPTIONS

5000k Colour Temperature 3-Hour Emergency Version Built-in Microwave Occupancy Detector No

1-10V Dimmable Available on Request **DALI** Dimmable Available on Request

CLEARANCE Stock - limited quantities - check before ordering. Order entire amount required first time as once sold, no more will be available as a discontinued product



Unit 2,
Delta Court,
Doncaster,
DN9 3GN
text_phone 03333 444 943
sales@theledstore.co | https://theledstore.co/

The 360 degree series post-top is a modern designed LED luminaire for column/post mounting at heights of 3 - 7m, suited to general open areas such as pedestrian areas, car parks and low-to-medium traffic urban applications.

IP65 RAL Black die-cast housing finished with a polybonate diffuser, the 360 degree luminaire gives all round uniform illumination with minimal light spillage, capable for reaching 20-30lux from typical 5-6m installations. Furthermore, luminaire compatible with standard external mains photocells for complete dusk-till-dawn control.

The unit is complete with base mount suitable for 76mm post top column-entry hence universally compatible. Additional benefits include 95lm/W efficacy, +55,000 hour maintenance free performance and minimal disturbance to nocturnal wildlife to the lack of UV/IR spectrum associated with LED photo-metric characteristics.