Unit 2,
Delta Court,
Doncaster,
DN9 3GN
text_phone 03333 444 943
sales@theledstore.co | https://theledstore.co/

IP65 LED Emergency Exit Bulkhead (TRADE BULK 10 PACK) 3h Maintained / Non-Maintained, Manual & Self-Test, LiFePO4 Battery c/w Self Adhesive Legend

~~£155.40~~ £118.80





IP65 LED Emergency Exit Bulkhead Light – Maintained / Non-Maintained, Manual & Self-Test, LiFePO4 Battery

The **IP65 LED Emergency Bulkhead Light** is a reliable and energy-efficient emergency lighting solution suitable for commercial, industrial and public buildings. Designed for both **maintained and non-maintained operation**, this emergency bulkhead is ideal for corridors, stairwells, exits, warehouses, offices, schools, retail units and communal areas.

With **manual test and self-test switchable functions**, this LED emergency bulkhead allows for easier routine testing and maintenance. The durable **IP65-rated housing** provides protection against dust and water, making it suitable for indoor and sheltered outdoor installations.

Powered by a long-life **LiFePO4 emergency battery**, this fitting offers improved safety, reliability and battery performance compared with traditional emergency lighting batteries.

Key Features

- **IP65 rated** for protection against dust and water
- Suitable for **maintained and non-maintained operation**
- Switch to choose between Manual Key Switch Test OR automatic self-test switchable (key switch or automatic periodic self test with status indicator lights to reduce maintenance)
- Long-life LiFePO4 lithium battery for low maintenance, ongoing use
- **c/w self adhesive legend kit - can be applied to suit any direction/orientation**
- 3h/180 Minute Energy-efficient **LED emergency lighting**
- Ideal for corridors, stairwells, exits and communal areas

Unit 2,
Delta Court,
Doncaster,
DN9 3GN
text_phone 03333 444 943
sales@theledstore.co | https://theledstore.co/

- Suitable for commercial, industrial and public buildings
- Durable bulkhead design for wall or ceiling mounting
- Reliable emergency illumination during power failure
- Ideal replacement for older emergency bulkhead fittings

Product Wattage	3W
Product Lumen	300Lm
Lumen/W	100
EM Wattage	1.2W
EM Lumen	150Lm
Kelvin	6500K
Beam Angle	120°
CRI	80
Lifetime	50,000 hours
Power Factor	0.46
Inrush Current at Start Up	Max. 2A
Product Voltage	220–240V
Hertz	50/60
Battery Spec.	LiFePO4 3.2V 1500mAh x1pc
Duration	3 hours / 180 minutes
Product Weight	0.48kg
Class	2