


**\*\*CLEARANCE\*\* Vandal Proof LED Bulkhead IP65 / IK10 - Outdoor Die-Cast Aluminium**



**£49.06 £30.00**



**STANDARD  
EMERGENCY  
MICROWAVE**



**IP65 / IK09**



**PRODUCT INFORMATION**

LED Type	SMD2835
Warranty	No warranty on clearance products
Part L Compliant	Yes
Dimensions	320mm x 320mm x 99mm

**TECHNICAL SPECIFICATIONS**

Power Consumption	18W
Input Voltage	100 - 280V AC
Power Factor	>0.95
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+40,000hrs
Ingress Protection	IP65

**LUMEN PERFORMANCE**

Luminous Efficiency	106lm/W
Beam Angle	120°

## PRODUCT INFORMATION

## TECHNICAL SPECIFICATIONS

## LUMEN PERFORMANCE

CRI (Colour Rendering Index)	>80Ra
Lumen Output	1900lm

### AVAILABLE OPTIONS

Colour Temperature	CW 6500-7000K
3-Hour Emergency Version	Available Variant
Built-in Microwave Occupancy Detector	Available Variant
1-10V Dimmable	Available Variant
DALI Dimmable	Available Variant

**\*\*CLEARANCE \*\*** A complete LED replacement suitable for stairwells, walk ways, undercrofts as well as outdoor use being IP65 rated. With an anti-glare frosted toughened diffuser for uniform, subtle light output up to 1900lm, this unit is designed to be a direct replacement for 28W 2D-flourescents, whilst boasting efficacy of up to 106lm/W. Hence energy savings over flourescent counterparts in the region of 35-40% with an equivalent reduction in utilities. Other benefits include minimised maintenance rated at 30,000 hours, high light output even in cold temperatures and minimised distrubance to wildlife due to non ultra violet light. Further options include intergal 3-hour emergency pack with self-test function as well as built in microwave sensore for intelligent occupancy control: adjustable dimming (up to 25%), sensitivy range (180° / 0.5m - 8m) and duration (10secs - 5mins).

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)