





# \*\*CLEARANCE\*\* LED Street Lights 120W - 6-8m Column Street Lighting Fixture

£130.80 £66.00



## **PRODUCT INFORMATION**

LED Type SMD3030 LEDs

Warranty No warranty on clearance products

Part L Compliant Yes

Dimensions 631mm x 215mm x 89mm

Weight 4.5kg

Socket Type 40/60mm Pole Side Entry
Equivalent to 6-8m 150W MHL / 250W SON

#### **TECHNICAL SPECIFICATIONS**

Power Consumption 120W
Input Voltage 110-280V AC
Power Factor >0.95

Operating Temperature -20°C to 50°C L70 Rated Lifetime +50,000hrs Ingress Protection IP67

## **LUMEN PERFORMANCE**

Luminous Efficiency110lm/WBeam Angle80° x 150°CRI (Colour Rendering Index)>80RaLumen Output13,100lm


# **AVAILABLE OPTIONS**

Colour Temperature Cool White (6500-7000K)

3-Hour Emergency Version No Built-in Microwave Occupancy Detector No

1-10V Dimmable Available on Request DALI Dimmable Available on Request

1 unit remaining ONLY





text\_phone 03333 444 943

[80° x 150°] 120W / 13,100lm LED Street Lighting series post-top is a minimalistic slimline LED street light Juminaire idesigned/ for column/post mounting at heights of 4 - 7m. IP67 design for exterior environments, with a low-profile, sleek silver anodised aluminium body for harsh weather environments, luminaire is for urban applications such as car-parks, pathways and pedestrian areas. PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further enhancing this 110lm/W luminaire to give optimum lux levels throughout. Furthermore, street light luminaire compatiable with standard mains photocells. Additional benefits of LED street lights as well as +50,000hour maintenance free performance, include minimal disturbance to nocturnal wildelife to the lack of UV/IR spectrum associated with LED photometric characteristics. LED Street Light unit includes box both cover plates to suit 40mm and 60mm side entry as standard. Furthermore, compatible with part number LSTPST-A, adjustable street light adaptor for 60-70mm columns which can also be used for angle adjustment of luminaire around 120°.